

Technical Data Sheet

Acrylic Sealant

Designed for sealing window and door frames, sealing of cracks in masonry, plaster, wood, sealing gaps between the tubes. used indoors and outdoors. Shows good adhesion to most construction materials. Can be painted with all types of paints, prevents corrosion of the metal. Thermal stability range from -25°C to $+80^{\circ}\text{C}$. Film formation time 5-10 minutes. Complete drying time of 24-48 hours (in 5 mm seams).

DIRECTIONS FOR USE:

Clean the surface from dust, grease and other contaminants. Cut the cartridge tip and screw the nozzle tip, cut it in relation to the desired seam width. Using the gun put sealant evenly over the seam. An optimum bead width of 5 mm is recommended. Use at temperatures between $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$. Store in a cool, dry areas and keep out of reach of children. Avoid direct sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Store at temperatures between $+5^{\circ}\text{C}$ to $+40^{\circ}\text{C}$, protect from frost.

Solvent-free, environmentally friendly.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Acryl
2	Density	1,6 g/cm ³
3	Color	White
4	Skin formation	5-10 minutes
5	Cutting time (5mm bead)	12-24 hours
6	Curing time	24-48 hours
7	Elongation at break	>100%
8	Shelf life	18 months
9	Application temperature	from +5°C to +40°C
10	Temperature resistance	from -25°C to +80°C