

## Technical Data Sheet

### Professional All-Weather Montage Foam

All-weather one-component polyurethane foam. Designed for professional use. The foam shows an excellent adhesion to most building materials: wood, concrete, stone, plastics, metal, etc. It is used to fill gaps in window and door frames, seal joints and gaps, insulation of pipes and wires, filling voids and holes. It has displays excellent sound and thermal insulation properties.

#### DIRECTIONS FOR USE:

Before and during the mounting, the can temperature should be maintained in the range of +10 to +25°C. Clean the surface from dust and dirt, lightly moisten surface with water. Shake well (at least 20 times). Remove the cover and fasten the can to the mounting gun. Make sure the connection is secure. During application, the flap of the can must be kept side down. Apply foam over 2/3 of the joint width. The foam, which has not solidified, may be removed with acetone or a special cleaner. The foam, which has solidified can be removed mechanically only. Use at ambient temperatures ranging from -10°C to +30°C. Store in a cool, dry place and out of reach of children. Avoid direct sunlight and artificial radiation heaters.

#### PRECAUTIONARY MEASURES:

Contains: 4,4-diphenylmethane diisocyanate. Harmful in contact with the respiratory system. Irritating to eyes and skin. During operation, it is recommended to use safety glasses, gloves, respiratory protection. If you get foam on skin or eyes, rinse with water and seek medical advice immediately. Use only in well-ventilated area; do not smoke while applying the foam. Do not disclose or burn container after using.

Shelf life - 12 months from date of manufacture.

The date of manufacture is indicated on the bottle.

TECHNICAL DATA:

<b>NO.</b>	<b>Item</b>	<b>Data</b>
1	Base	Polyurethane
2	Density	17-27 kg/m <sup>3</sup>
3	Color	white, light-yellow
4	Skin formation	5-15 minutes
5	Cutting time (30mm bead)	20-40 minutes
6	Curing time	12-24 hours
7	Expansion	30-100%
9	Shelf life	12 months
10	Application temperature	from -10°C to +30°C
11	Temperature resistance	from -50°C to +100°C