

## Technical Data Sheet

### Polymer Glue

Homogeneous transparent adhesive with a characteristic odor. Designed for bonding polystyrene foam products, plastic products, wood products, ceramics, cork flooring, parquet insulation on various types of smooth surfaces such as concrete, brick, stucco, plaster, plasterboard, wood, etc. Anti-frost.

#### INSTRUCTIONS FOR USE AND STORAGE:

The surfaces intended for gluing must be smooth, dry and degreased. On both surfaces of the adhesive applied glue by dots or stripes and smoothed with special spatula, 30-60 seconds to press them firmly. Fixing time is 2-3 hours, completely drying time is 12-24 hours. Use at a temperature above zero. Store at a temperature above zero in the original container tightly closed.

#### PRECAUTIONARY MEASURES:

Avoid storage in places accessible for children.

Keep away from direct sunlight.

The date of manufacture is indicated on the bottle.

Shelf life - 12 months.

## TECHNICAL DATA:

NO.	Item	Data
1	Base	Polymer
2	Density	0,95 g/cm <sup>3</sup>
3	Color	transparent
4	Skin formation	5-10 minutes
5	Curing time	12-24 hours
6	Bonding strength (wood-wood method)	>25 kg/cm <sup>2</sup>
7	Shelf life	12 months
8	Application temperature	from +5°C to +40°C
9	Temperature resistance	from -25°C to +80°C