

Technical Data Sheet

Glue For Bamboo

Environmentally friendly, solvent-free adhesive. Transparent after complete solidification. Designed specifically for bonding roll and tile cork and bamboo products, excellent for bonding glass, mosaic tile and other heavy decorative items that require transparent seam.

DIRECTIONS FOR USE:

Clear the work surface from dust and moisture. Apply glue to the surface in dots or stripes. It is recommended to be applied with the use of a notched trowel. Firmly press bonding surfaces to each other and fix them in this position until the adhesive dries. Fixing time of glue is 5-10 minutes, Complete drying time is 24-48 hours. Use at temperatures ranging from +5°C to +40°C. Store in a cool, dry area and keep out of reach of children. Avoid direct contact with sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Store at temperatures between +5°C to +40°C, protect from frost.

Solvent-free, environmentally friendly.

The date of manufacture is indicated on the bottle.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Acryl
2	Density	1,0 g/cm ³
3	Color	transparent
4	Skin formation	5-10 minutes
5	Curing time	12-24 hours
6	Bonding strength (wood-wood method)	21 kg/cm ²
7	Shelf life	18 months
8	Application temperature	from +5°C to +40°C
9	Temperature resistance	from -25°C to +80°C