

Technical Data Sheet

Super Strong Fixing Glue

Universal construction adhesive. Specially designed for bonding of heavy constructions: ceramic tile, wood and plasterboard, flooring, linoleum, carpet. It features superstrong fixation. Suitable for interior and exterior use. Water-resistant.

DIRECTIONS FOR USE:

Clear the work surface from dust and moisture. Apply glue to the surface in dots or stripes. It is recommended to use a notched trowel for application. Firmly press bonding surfaces to each other and hold them together until the adhesive dries. Fixing time of glue is 5-10 minutes, the time of complete setting is 24-48 hours. Use at temperatures between +5°C to +40°C. Store in a cool, dry area and keep out of reach of children. Avoid direct exposure of container to sunlight and artificial radiation heaters.

PRECAUTIONARY MEASURES:

Store at temperatures between +5°C to +40°C, protect from frost.

Solvent-free, environmentally friendly.

The date of manufacture is indicated on the bucket.

Shelf life - 18 months.

TECHNICAL DATA:

NO.	Item	Data
1	Base	Acryl
2	Density	1,5 g/cm ³
3	Color	White
4	Skin formation	5-10 minutes
5	Curing time	12-24 hours
6	Bonding strength (wood-wood method)	13 kg/cm ²
7	Shelf life	18 months
8	Application temperature	from +5°C to +40°C
9	Temperature resistance	from -25°C to +80°C